

10/826,000

5. Page 3, rewrite the paragraph beginning at line 22 as follows:

Referring to the drawings, Figure 1 illustrates a ~~Jeep~~ JEEP -type vehicle 10 having a door carrier 12 mounted at a conventional rearwardly extending ~~Reese~~ REESE -type a hitch 14. As shown in Figure 11, a typical vehicle 10 is provided with a pair of removable side doors 16 mounted a vertically spaced door hinge set 18. As shown in Figure 6, the doors 16 of such vehicles are characterized by a pair of downwardly projecting circular hinge pins 20 carried on exterior door mounted brackets 21. The hinge pins 20 are journaled in hinge sleeves 22 mounted at the front vehicle door frame 24. The doors 16 also include a door latch mechanism 26 operated by exterior and interior handles 28. The latch mechanism 26 releasably engages a transverse cylindrical lock pin 30 projecting forwardly from the rear door frame 32 for locking and unlocking the door.

BSH 7/2/07

6. Page 4, rewrite the paragraph beginning at line <sup>19</sup>~~20~~ as follows:

Referring to Figures 2 through 5, the carrier 12 includes a base frame 40 and a pair of laterally spaced pivoting side frames 42. The base frame 40 is connected at a front pivot assembly 44 to a mounting tube 46 for pivotal movement about a transverse horizontal axis 47. The mounting tube 46 has a front end that is conventionally telescopically